

## **Professional**

## **Single Stage Belt Drive Stationary Series**

- Oil lubricated, single stage cast iron pumps.
- Single phase induction motors with overload protection.
- 1/2" outlet ball valve and 1/4" drain ball valve on all units.
- Accessories such as automatic water drain, vibration damper, and regulator filter are available.
- Ideal for home and professional applications.







Model		PK-6060V	PK-6560V	PK-7060V			
	H.P.	3	5	6.5			
Electric Motor	R.P.M	3450 / 56	3450 / 56	3450 / 182			
	Volt./ Phase/ Amp.	208-230/ Single/ 16.6-15	208- 230/ Single/ 21-19	208- 230/ Single/ 28-24			
Pump R.P.M		980	1180	1130			
Max. Working PSI.		135	135	135			
C.F.M.	@ 40 PSI	12.6	17	21			
C.F.M.	@ 90 PSI	11.3	15.5	19.5			
	Gal.	60	60	60			
TANK	Style	Vertical	Vertical	Vertical			
	Code	ASME / CRN	ASME / CRN	ASME / CRN			
Weight (Lbs) Remark Magnetic Starter		305	325	360			
				Extend Water Drain			
		n/a	Option	Combo Pressure Switch Starter			

## PUMA INDUSTRIES, INC

1992 Airways Blvd. Memphis, TN 38114 TEL:1-901-744-7979 FAX:1-901-744-7579 e-mail:sales@pumaaircenter.com http://www.pumaairusa.com



*	These	prod	ucts	are	protected	bv	one	or	more	paten	ts.	Ot	hers	mav	be	pendin	ıa.
	243300000					,			39900000					,			9